



Size A	Part No.*	Across Flats B Max. Min.	Thickness C Max. Min.	Available Style	Bearing Dia. Min.	Proof Load Min. Lb.	1 st Install Max. In.-lb.	1 st Removal Min. In.-lb.	3 rd Removal Min. in.-lb.	Weight /each Lb.	Carton Qty.
1 1/8-7	112CFROC#	1.687	0.999	X	1.603	115,000	1200	150	50	0.315	90
1 1/8-12	112FFROC#	1.631	0.939	X		128,000					
1 1/4-7	125CFROC#	1.875	1.094	X	1.781	145,000	1320	188	60	0.417	60
1 1/4-12	125FFROC#	1.812	1.030	X		161,000					
1 3/8-6	137CFROC#	2.062	1.206	Y	1.959	173,000	1620	220	70	0.541	50
1 3/8-12	137FFROC#	1.994	1.138	Y		197,000					
1 1/2-6	150CFROC#	2.250	1.317	X	2.123	211,000	1800	260	90	0.729	35
1 1/2-12	150FFROC#	2.175	1.245	X		237,000					
1 5/8-5	162CFROC#	2.430	1.416	Y	2.233	241,000	2000	340	100	0.968	25
1 5/8-12	162FFROC#	2.350	1.364	Y		281,000					
1 3/4-5	175CFROC#	2.625	1.540	X	2.411	285,000	2100	410	110	1.23	20
1 3/4-12	175FFROC#	2.538	1.460	X		328,000					
2-4.5	200CFROC#	3.000	1.763	X	2.755	375,000	2500	470	120	1.85	15
2-12	200FFROC#	2.900	1.675	X		433,000					
2 1/4-4.5	225CFROC#	3.375	1.986	Y	3.100	Hardness HRC 26-36	2800	530	130	2.47	10
2 1/4-12	225FFROC#	3.263	1.890	Y							
2 1/2-4	250CFROC#	3.750	2.193	X	3.444		3000	590	150	3.42	7
2 1/2-12	250FFROC#	3.625	2.135	X							
3-4	300CFROC#	4.500	2.654	Y	4.133		3300	710	200	6.46	4
3-12	300FFROC#	4.350	2.534	Y							
3 1/2-4	350CFROC#	5.250	3.100	Y	4.821		3500	830	240	10.3	2
3 1/2-12	350FFROC#	5.075	2.964	Y							
4-4	400CFROC#	6.000	3.545	Y	5.510		3600	950	280	15.3	1
4-12	400FFROC#	5.800	3.393	Y							

*Coating Codes (substitute for “#” in the part number).
Other available finishes may not be listed.

[blank] – Unfinished Plain
1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
4 – Phosphate/Oil per ASTM F 1137 Grade D
C – Commercial Cadmium/Clear
Y – Commercial Zinc/Yellow
Z – Commercial Zinc/Clear

Notes:

- Items over 1 1/2” dia. dimensions per ASME B18.2.2-2010 Table 4 Hex Nut
- Items up to and including 1 1/2” dia. are compliant to all requirements of IFI 100/107 2002 for Grade C All Metal Prevailing Torque Hex Locknuts.

CollarPlus® LOCKNUTS GRADE C



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	B