



Size A	Part No.*	Across Flats B		Thickness C		Washer Dia. D		Weight /1000 Lb.	Carton Qty.
		Max.	Min.	Max.	Min.	Across Corners Min.	Max.		
#4-40	4CKLN2#	0.250	0.241	0.098	0.087	0.275	0.286	1.2	34,000
#6-32	6CKLN2#	0.312	0.302	0.114	0.102	0.344	0.348	2.6	15,000
#8-32	8CKLN2#	0.343	0.331	0.130	0.117	0.378	0.380	2.8	14,000
#10-24	10CKLN2#	0.375	0.362	0.130	0.117	0.413	0.406	4	10,000
#12-24	12CKLN2#	0.438	0.423	0.220	0.210	0.482	0.510	6.6	6,000
1/4-20	25CKLN2#	0.438	0.428	0.193	0.178	0.482	0.505	8.4	4,700
1/4-28	25FKLN2#						0.493		
5/16-18	31CKLN2#	0.500	0.489	0.340	0.315	0.557	0.591	13.2	3,000
5/16-24	31FKLN2#						0.571		
3/8-16	37CKLN2#	0.562	0.551	0.336	0.320	0.648	0.656	19.8	2,000
3/8-24	37FKLN2#						0.648		

*Coating Codes (substitute for “#” in the part number).
Other available finishes may not be listed.

[blank] – Unfinished Plain

1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C

2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT

3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A

4 – Phosphate/Oil per ASTM F 1137 Grade D

C – Commercial Cadmium/Clear

Y – Commercial Zinc/Yellow

Z – Commercial Zinc/Clear

Notes:

1. Threads per ASME B1.1 2003.01.01
2. Material per SAE J995 (Nut) and SAE J403 1050 (Washer)
3. A manufacturer's I.D. may appear on the locknut. If there is an I.D. mark, it may be Aztech's or another manufacturer's.

K-loc Style GRADE 2



Date	By	Scale	Units	Type	Rev.
10-22-14	SEK	None	Inch	Sales	C