



Size <b>A</b>	Part No.*	Across Flats <b>B</b> Max. Min.	Thickness <b>C</b> Max. Min.	Flange Dia. <b>D</b> Max. Min.	Wrench Height Min.	Proof Load Min. Lb.	Seating Torque In.-Lb.	Weight /1000 Lb.	Carton Qty.
1/4-20	25CLSLH#	0.438	0.312	0.728	0.15	2900	108	13.9	2800
1/4-28	25FLSLH#	0.428	0.281	0.700		3300	120		
5/16-18	31CLSLH#	0.500	0.375	0.820	0.20	4700	168	19.0	1800
5/16-24	31FLSLH#	0.489	0.343	0.790		5200	180		
3/8-16	37CLSLH#	0.562	0.406	0.915	0.24	7000	324	27.0	1300
3/8-24	37FLSLH#	0.551	0.390	0.885		7900	348		
1/2-13	50CLSLH#	0.750	0.515	1.131	0.29	12,800	744	59.5	575
1/2-20	50FLSLH#	0.736	0.485	1.100		14,400	816		

\*Coating Codes (substitute for “#” in the part number).  
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

**Notes:**

1. These items are compliant to all requirements of ASME B18.16.4-2008 for Large Serrated Flange Locknuts.

## LARGE SERRATED FLANGE LOCKNUTS



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	B