



Size <b>A</b>	Part No.*	Across Flats <b>B</b> Max. Min.	Thickness <b>C</b> (ref.)	Across Corners Min.	Wrench Height <b>D</b> Min.	Proof Load Min. Lb.	1 <sup>st</sup> Install Max. In.-lb.	1 <sup>st</sup> Removal Min. In.-lb.	3 <sup>rd</sup> Removal Min. in.-lb.	Weight /1000 Lb.	Carton Qty.
#6-32	6CNKMA#	0.314	0.297	0.344	0.200	820	8.0	1.5	0.5	3.5	11000
#6-40	6FNKMA#	0.302				900					
#8-32	8CNKMA#	0.346	0.353	0.378	0.225	1250	12.0	2.0	1.0	4.7	8000
#8-36	8FNKMA#	0.334				1350					
#10-24	10CNKMA#	0.377	0.363	0.413	0.234	1550	17	2.5	1.0	6.0	6000
#10-32	10FNKMA#	0.365				1800					
1/4-20	25CNKEA#	0.440	0.480	0.488	0.290	2900	40	5.0	1.5	9.5	4000
1/4-28	25FNKEA#	0.428				3300					
5/16-18	31CNKEA#	0.502	0.503	0.557	0.343	4700	80	8.0	2.5	13	2500
5/16-24	31FNKEA#	0.490				5200					
3/8-16	37CNKEA#	0.564	0.622	0.628	0.415	7000	110	12.0	4.0	18	2000
3/8-24	37FNKEA#	0.553				7900					

\*Coating Codes (substitute for “#” in the part number).  
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

Notes:

1. These items are compliant to the performance and material requirements of ASME B18.16.6 – 2008 Nut Grade NE2.

## NYLON CAP (NKE, NKM) LOCKNUTS GRADE NE2



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	B