



Size A	Part No.*	Across Flats B Max. Min.	Thickness C Max. Min.	Wrench Height D Min.	Flange Dia. E Max.	Proof Load Min. Lb.	1 st Install Max. In.-lb.	1 st Removal Min. In.-lb.	3 rd Removal Min. in.-lb.	Weight /1000 Lb.	Carton Qty.
1/4-20	25CFN-G#	0.438 0.428	0.279 0.300	0.140	0.560	4750	40	5.0	1.5	8.8	4000
5/16-18	31CFN-G#	0.500 0.489	0.339 0.364	0.170	0.680	7850	80	8.0	2.5	14.7	2300
3/8-16	37CFN-G#	0.562 0.555	0.395 0.425	0.200	0.810	11,600	110	12	4.0	22	1500
7/16-14	43CFN-G#	0.688 0.675	0.456 0.493	0.230	0.930	15,900	135	17	5.0	36.1	900
1/2-13	50CFN-G#	0.750 0.736	0.531 0.554	0.260	1.070	21,300	204	22	7.5	52.1	650
5/8-11	62CFN-G#	0.938 0.922	0.660 0.690	0.320	1.330	33,900	420	39	12.5	106	350
3/4-10	75CFN-G#	1.125 1.088	0.790 0.825	0.380	1.585	50,100	540	58	20	185	200

*Coating Codes (substitute for “#” in the part number).
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

Notes:

1. These items are compliant to all requirements of IFI 100/107 for Grade G Hex Flange Locknuts

FLANGE NYLON INSERT LOCKNUTS GRADE G



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	B