



Size A	Part No.*	Across Flats B		Thickness C		Across Corners Min.	Proof Load Min. Lb.	Install or Removal Torque		Weight /1000 Lb.	Carton Qty.
		Max.	Min.	Max.	Min.			Max. In.-lb.	Min. in.-lb.		
#6-32	6CNM-A#	0.313	0.188	0.339	1100	10	1.0	0.26	15,000		
#6-40	6FNM-A#	0.305	0.168		1220						
#8-32	8CNM-A#	0.345	0.239	0.374	1680	15	1.5	0.42	10,000		
#8-36	8FNM-A#	0.336	0.219		1770						
#10-24	10CNM-A#	0.376	0.249	0.410	2100	18	2.0	0.50	8000		
#10-32	10FNM-A#	0.367	0.229		2400						
#12-24	12CNM-A#	0.439	0.328	0.482	2900	25	2.5	0.92	4200		
#12-28	12FNM-A#	0.430	0.298		3250						

*Coating Codes (substitute for “#” in the part number).
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

Notes:

1. Threads per ASME B1.1 UN-2B
2. Prevailing Torque Performance per ASME B18.16.6

NYLON INSERT (NM) LOCKNUTS



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	C