



Size A	Part No.*	Across Flats B		Thickness C	Across Corners	Proof Load	Install or Removal Torque	Breakaway Torque	Weight /1000	Carton Qty.
		Max.	Min.							
#6-32	6CNTMA#	0.313	0.305	0.140	0.339	560	10	1.0	0.19	24,000
#6-40	6FNTMA#	0.305	0.110	0.110		620				
#8-32	8CNTMA#	0.345	0.336	0.187	0.374	860	15	1.5	0.30	13,000
#8-36	8FNTMA#	0.336	0.157	0.157		910				
#10-24	10CNTMA#	0.376	0.367	0.187	0.410	1080	18	2.0	0.35	12,00
#10-32	10FNTMA#	0.367	0.157	0.157		1230				
#12-24	12CNTMA#	0.439	0.430	0.218	0.482	1490	25	2.5	0.54	7500
#12-28	12FNTMA#	0.430	0.188	0.188		1590				

*Coating Codes (substitute for “#” in the part number).
Other available finishes may not be listed.

- [blank] – Unfinished Plain
- 1 – Zinc/Yellow per ASTM F1941 -10 Fe/Zn 5C
- 2 – Zinc/Clear per ASTM F1941 -10 Fe/Zn 5AT
- 3 – Cadmium/Clear per ASTM F1941 -10 Fe/Cd 5A
- 4 – Phosphate/Oil per ASTM F 1137 Grade D
- C – Commercial Cadmium/Clear
- Y – Commercial Zinc/Yellow
- Z – Commercial Zinc/Clear

Notes:

1. Threads per ASME B1.1 UN-2B
2. Prevailing Torque Performance per ASME B18.16.6

NYLON INSERT (NTM) LOCKNUTS



Date	By	Scale	Units	Type	Rev.
2-17-14	MJK	None	Inch	Sales	C